SPXFLOW



PD Pump Specialized Features

What

- Available for Universal 1, 2 and UL Series Pumps- AL6XYN and 17-4
- Metal detectable o-rings
- USP Class VI elastomers
- Suction vent/throttle bushing
- Surface coatings diamond and armolloy
- Enhanced surface finishes up to 15 Ra
- Custom port lengths and connections
- Specialized shafts for abrasive and corrosive applications
- Specialized seals for products that are difficult to seal
- Internal pressure relief options
- Rectangular flanges available

Why

- Customized pumps to suit specific application needs





Benefits

- Unique pump solutions for a wide variety of customer needs
- Increased pump life expectancy
- Metal detectable o-rings to ensure product safety

DON'T FORGET TO USE OTHER GENUINE SPX FLOW PARTS TO ENSURE YOUR EQUIPMENT CONTINUES TO PERFORM AT OPTIMUM LEVELS.



Based in Charlotte, North Carolina, SPX FLOW, Inc. (NYSE: FLOW) is a multi-industry manufacturing leader. For more information, please visit www.spxflow.com



SPX FLOW 611 Sugar Creek Road, Delavan, WI 53115 P: (262) 728-1900 or (800) 252-5200 E: leads@spxflowleads.com • www.spxflow.com

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction, dimensional data and certifications as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit www.spxflow.com.

The green ">" and ">" are trademarks of SPX FLOW, Inc.

WCB_Pumps-PD-Specialized-Features_FB-0047_FLR_US Version 04/2019 COPYRIGHT © 2019 SPX FLOW, Inc.

>Waukesha Cherry-Burrell[®]

SPXFLOW

Contact your local Distributor for further information:

(AFFIX DISTRIBUTOR LABEL HERE OR FILL IN CONTACT DETAILS)



